

**RESOLUTION No. R-2021-02**

**A RESOLUTION AUTHORIZING THE MAYOR AND/OR THE CITY CLERK OF THE CITY OF WARD TO ENTER INTO A CONTRACT TO PURCHASE A UTILITY TRACTOR**

**WHEREAS, THE CITY OF WARD** desires to purchase a commercial grade tractor to replace one that is over 20 years old and requires constant maintenance to operate; and,

**WHEREAS,** maintaining city equipment is a priority, it becomes necessary from time-to-time to replace worn out equipment that has become more and more expensive to maintain; and,

**WHEREAS,** upon receipt of the new tractor, the replaced tractor will be placed on govdeals.com for sale to the highest bidder. After 60 days on govdeals.com, it will be placed for sale on the local market and sold via sealed bid.

**NOW, THEREFORE, IT IS RESOLVED THAT THE CITY COUNCIL OF THE CITY OF WARD** hereby declares that the Mayor and/or the City Clerk may enter into a contract with Brunos Powersports in Cabot, AR to purchase one new Massey Ferguson Series MF2605H 4X4 Utility Tractor with canopy as specified in the quote for a price of not more than **\$22,900.00** plus tax.

Said resolution has been properly introduced and the vote was:

PASSED


YEAS 4 NAYS 2

DATE: January 18, 2021

APPROVED:

  
\_\_\_\_\_  
Charles Gastineau, Mayor

ATTEST:

  
\_\_\_\_\_  
Courtney Ruble, City Clerk

City Seal





## BRUNO'S POWERSPORTS,LLC

### PROPOSAL FOR CITY OF WARD

1 MASSEY FERGUSON 2605H 4X4 WITH CANOPY \$22900.00

ANY QUESTIONS PLEASE CONTACT NATHAN PRUSS AT 501-580-4206 OR 501-605-1210



9514 AJ Patton Road  
Cabot, Ar 72023

PHONE 501-605-1210  
FAX 501-941-0115  
EMAIL [brunosatv@hotmail.com](mailto:brunosatv@hotmail.com)  
WEB SITE [www.brunosatv.com](http://www.brunosatv.com)

# MF2605H

(F.O.B. PORT OF ENTRY)



MASSEY FERGUSON®

## TRACTOR FEATURES

### ENGINE SYSTEM

- Simpson 2.6L, T4 Final, EPA & CARB Certified
- 3 Cylinder
- Turbocharged, Intercooled, HPCR Fuel Injection
- 55 (40.4 kW) PS Gross Engine Horsepower @ 2000 RPM
- 46 (33.8 kW) PTO Horsepower @ 2000 RPM

### FRONT AXLE - Two Factory Options

- 2 Wheel Drive with Telescopic Adjustment  
OR
- 4 Wheel Drive with Planetary Reduction Final Drives

### POWER TRAIN

- **2wd Transmission** - 8x2 Sideshift - Sliding Gear - Transmission Shift Control Lever on Right Side and Range Box Shift Control Lever on Left Side
- Rear Axle Bevel Gear, Single Reduction Type
- **4wd Transmission** - 8x8 Synchro Shuttle with ComfiMesh™ - Transmission Shift Control Lever on Right Side and Range Box Shift Control Lever on Left Side
- Mechanical F-R Shuttle Lever Left Side of Steering Wheel
- Outboard Planetary Final Drives
- Brakes - Internal Multi Wet Disc with Mechanical Actuation
- Parking Brake - Mechanical Hand Lever

### PTO

- **2wd** - Live, 540 RPM, 6 Spline shaft with Dual Stage Dry Clutch
- **4wd** - Independent PTO, 540 RPM, 6 Spline Shaft with Lever Operated Split Torque Clutch

### THREE POINT LINKAGE

- Extendable Lower Links with Dual Tumbuckle Adjustment -Category I/II Cross Drilled Ball Ends
- Sway Chain Stabilizers

### HYDRAULICS

- Hydrostatic Steering with Separate Reservoir
- Ferguson 3-Point Hitch System
- 3-Point Hitch Pump Flow (4.2 GPM) \*
- Draft, Position and Response Control
- Single Spool Valve Included
- Hydraulic Pump Flow 10.6 GPM at Rear Remote \*
- Maximum Hydraulic Flow 15.7 GPM (59.5 LPM) (Steering, 3-Point and Auxiliary Combined)

### ELECTRICAL

- Headlights
- Single Rear Work Light
- Safety Lights
- 7 Pin ASAE Outlet

### OPERATORS ENVIRONMENT

- Straddle Mount
- Grammar Seat that Inclines as it Moves Rearward
- Retractable Seatbelt
- Folding ROPS
- Suspended Foot Pedals
- Ground-Level Fuel Tank

### OTHER STANDARD FEATURES

- Tilting One Piece Hood
- Swinging Drawbar
- Tool Box
- Drawbar Clevis

\*Manufacturer's Estimate

## LOADER FEATURES

### MF FLx2815 Pin Type Style Loader

- One Piece Main Frame with Tapered Arms and Single Cross Member
- Quick Attach Loader Frame Mount with Pin Lock
- Built-in Parking Stands
- (2) 2.76 inch Double Acting Lift Cylinders
- (2) 2.56 inch Double Acting Bucket Cylinders
- Hydraulic Valves with Integrated Joystick Mount to Right Side Loader Subframe
- Hydraulic Lines Routed Inside Main Frame for Protection and Visibility
- Galvanized Steel Bushings with Recessed Grease Points
- 72-inch Standard Duty Skid Steer Bucket
- **Fits all MF2600H Series 2wd Tractors**
- Maximum Lift Height: 111 Inches at Pivot Pin
- Lift Capacity to Full Height at Pivot Pin: 2,810 lbs
- Breakout Force: 4,240 lbs at Pivot Pin
- Rated Hydraulic Pressure: 2350 PSI
- Grille Guard Standard

### MF911X Loader

- One Piece Main Frame with Tapered Arms and Single Cross Member
- Quick Attach Loader Frame Mount with Pin Lock
- Built-in Parking Stands
- (2) 2.4 inch Double Acting Lift Cylinders
- (2) 2.4 inch Double Acting Bucket Cylinders
- Hydraulic Valves with Integrated Joystick Mount to Right Side Loader Subframe
- Hydraulic Lines Routed Inside Main Frame for Protection and Visibility
- Galvanized Steel Bushings with Recessed Grease Points
- Universal Skid Steer or Euro Hook Type Implement Attachments
- **Fits all MF2600H Series 4wd Tractors**
- Maximum Lift Height: 115 inches at Pivot
- Lift Capacity to Full Height at 31.5 inches Forward of Pivot Pin: 1510 lbs
- Breakout Force: 2750 lbs
- Rated Hydraulic Pressure: 2755 PS
- Grille Guard Standard